

## Wetting and Dispersing Agent

### GENERAL INFORMATION

Disponer 9258 is a copolymer with acidic groups, it is particularly effective in the wetting of inorganic pigment or filler therefore reduces viscosity of coating system.

### PHYSICAL PROPERTIES

Composition	solution of a copolymer with acidic groups
Appearance	yellow clear liquid
Colour value	≤ 2 Gardner
Non-volatile content	48 - 52%
Solvent	Dimethyl carbonate
Specific gravity	ca 1.1
Acid value	40 – 55 mg KOH/g (as received)

### APPLICATIONS

- acrylic PU
- acrylic / melamine
- car refinish
- coil coatings

### KEY PROPERTIES

- Disponer 9258 is an excellent wetting and dispersing agent for the stabilization of inorganic pigments in coating system.
- Disponer VP-9258 does not cause yellowing of paint film.
- Good stability at low temperature.
- Aromatic solvent free and organic tin free.

### INCORPORATION

- Stabilize inorganic pigments and reduce millbase viscosity.
- No influence on yellowing of paint film.
- Please check the optimum dosage and test compatibility before use.

### LEVELS OF USE

- Inorganic pigment : 2 - 5% based on pigment.
- Organic pigment : 2 - 5% based on pigment.

### HANDLING AND SAFETY

- As it contains solvents, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check to MSDS.

### STORAGE RECOMMENDATIONS

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C to 40°C.

### PACKAGING

Net Weight: 200 kg / 25 kg

*NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.*

*© Copyright 2006, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.*

*® Trademark of Elementis Specialties, Inc.*

[www.elementis-specialties-asia.com](http://www.elementis-specialties-asia.com)

B03 Dec-10

## **SHELF LIFE**

Disponer 9258 has a shelf life of 12 months from date of manufacture.

## **QUALITY ASSURANCE**

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees that all operations are conducted according to the stipulated standards.

---

### **Elementis Specialties, Asia**

#### **USA Head Office**

**Elementis Specialties, Inc.**  
329 Wyckoffs Mill Road  
Hightstown, NJ 08520, USA  
Tel.: +1 609 443 2500  
Fax.: +1 609 443 2422

#### **Asia Head Office China**

**Deuchem (Shanghai) Chemical Co., Ltd.**  
99, Lianyang Road, Songjiang Industrial  
Zone, Shanghai, China 201613  
Tel.: +86 21 57740348  
Fax.: +86 21 57743563

#### **Taiwan**

**Deuchem Co., Ltd.**  
92, Kuang-Fu North Road, Hsinchu  
Industrial Park, Hukou, Hsinchu, Taiwan  
Tel.: +886 3 5984035  
Fax.: +886 3 5983301

#### **Malaysia**

**Elementis Specialties Inc.**  
Lot PT 55, 64 & 65,  
Jalan Hulu Tinggi 26/6, Seksyen 26,  
40400 Shah Alam, Selangor Darul Ehsan,  
Malaysia  
Tel.: +603 5191 9979  
Fax.: +603 5191 6811