

A water dispersible foam control agent for rubber applications

PHYSICAL PROPERTIES

Composition	a blend of hydrophobic silica, emulsifiers and mineral oil
Colour / Form	opaque off-white liquid
Flash Point	165 °C
Specific gravity	0.90
Viscosity, Brookfield	ca.300 cps

KEY PROPERTIES

DAPRO[®] AP 7072 is effective in high quality rubber applications and provides excellent foam suppression and defoaming performance.

DAPRO[®] AP 7072 is readily dispersible in water.

INCORPORATION

DAPRO[®] AP 7072 shows excellent compatibility and is suitable to use in the let down stage of sensitive coatings systems where film properties are critical. A ladder study should be carried out to optimize the loading level.

LEVELS OF USE

Typically 0.2 - 1.0 % on total weight, but should be optimized by testing.

HANDLING AND SAFETY

Before using this product please consult our Material Safety Data Sheet (MSDS) for information on safe handling and storage.

MSDS can be found on the company website at www.elementis-specialties-asia.com.

STORAGE RECOMMENDATIONS

Must be mixed prior to use

Under adequate storage conditions, can be stored for at least 24 months in a closed container. Store between 50 °F - 100 °F (10 °C - 38 °C). If frozen thaw at room temperature and mix well. Detailed information on handling and safety can be found in the material safety data sheet. Handle in accordance with good industrial hygiene and safety practices.

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2006, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

® Trademark of Elementis Specialties, Inc.

www.elementis-specialties-asia.com

B01 Jun-16

SHELF LIFE

DAPRO[®] AP 7072 has a shelf life of 2 (two) years from date of manufacture.

QUALITY ASSURANCE

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees that all operations are conducted according to the stipulated standards.

Elementis Specialties

Asia Head Office China

Deuchem (Shanghai) Chemical Co., Ltd.
99, Liyang Road,
Songjiang Industrial Zone,
Shanghai, China 201613
Tel.: +86 21 57740348
Fax.: +86 21 57743563

Taiwan

Deuchem Co., Ltd.
92, Kuang-Fu North Road,
Hsinchu Industrial Park,
Hukou, Hsinchu, Taiwan
Tel.: +886 3 5984035
Fax.: +886 3 5983301

Malaysia

Elementis S.E.A. (Malaysia) Sdn. Bhd.
(1095769-X)
62-1, Jalan Tasik Utama 5,
Medan Niaga Tasik Damai,
Sungai Besi, 57000 Kuala Lumpur,
Wilayah Persekutuan, Malaysia
Tel.: +603-9054 6690
Fax.: +603-9054 6698

India

Elementis Specialties (India) Pvt. Ltd.
Unit B, Ground Floor,
Jaswanti Landmark,
Mehra Industrial Estate,
L.B.S Marg, Vikhroli (West),
Mumbai 400 079, India
Tel.: + 91 22 67421251
Fax.: + 91 22 67421252