

Waterborne Adhesion Promoter

GENERAL INFORMATION

DAPRO[®] ACP-16W is a waterborne adhesion promoter, which is designed for improving adhesion of waterborne coatings and inks on polypropylene (PP) substrates.

PHYSICAL PROPERTIES

Composition	acrylic modified chlorinated polyolefin
Appearance	milky white to milky yellow liquid
Non-volatile content	28 - 32 %
Solvent	water
Specific gravity	ca. 1.03
pH value	7 - 9

APPLICATIONS

Waterborne coatings and inks of polypropylene.

KEY PROPERTIES

- To improve adhesion on polypropylene substrates
- Emulsifier free

INCORPORATION

Directly used as sole binder or cooperate with other binders to produce PP primer. The compatibility and dosage should be tested before use.

LEVELS OF USE

Used as sole binder or 50 to 100 % of total binder.

HANDLING AND SAFETY

- The product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check to MSDS.

STORAGE RECOMMENDATIONS

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 5°C and 40°C.

PACKAGING

Net Weight: 200 kg / 25 kg

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2006, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

® Trademark of Elementis Specialties, Inc.

www.elementis-specialties-asia.com

B01 May-11

SHELF LIFE

DAPRO[®] ACP-16W has a shelf life of 8 months from date of manufacture.

QUALITY ASSURANCE

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees the all operations are conducted according to the stipulated standards.

Elementis Specialties

Asia Head Office China

Deuchem (Shanghai) Chemical Co., Ltd.
99, Lianyang Road,
Songjiang Industrial Zone,
Shanghai, China 201613
Tel.: +86 21 57740348
Fax.: +86 21 57743563

Taiwan

Deuchem Co., Ltd.
92, Kuang-Fu North Road,
Hsinchu Industrial Park,
Hukou, Hsinchu, Taiwan
Tel.: +886 3 5984035
Fax.: +886 3 5983301

Malaysia

Elementis S.E.A. (Malaysia) Sdn. Bhd.
(1095769-X)
62-1, Jalan Tasik Utama 5,
Medan Niaga Tasik Damai,
Sungai Besi, 57000 Kuala Lumpur,
Wilayah Persekutuan, Malaysia
Tel.: +603-9054 6690
Fax.: +603-9054 6698

India

Elementis Specialties (India) Pvt. Ltd.
Unit B, Ground Floor,
Jaswanti Landmark,
Mehra Industrial Estate,
L.B.S Marg, Vikhroli (West),
Mumbai 400 079, India
Tel: + 91 22 67421251
Fax: + 91 22 67421252